



ECOGEM rippleSHIELD S9041TC RS - 10W

Dimmable 10 watt LED downlight with selectable CCT and rippleSHIELD

Application

Ideal for any residential or commercial interior space, experiencing nuisance ripple induced flicker

Design Specifications

- Combined with the SAL SDD400SFI dimmer, the rippleSHIELD Coolum eliminates ALL nuisance non-visible and visible flicker caused by ripple injection
- Remote rippleSHIELD dimmable LED driver, with smooth dimming performance down to 1.0% of light output, designed with flex and plug
- Selectable CCT 3000K/4200K/5700K
- Stylish white powder coat finish colour trim options: (S9041 BK RING), (S9041 SN RING), (S9041 SL RING).
- IC - 4 rated, double insulated
- Need more info.....slide to the FAQ's below



Performance

- Dimmable - **YES**
- Dimmer Type - **Dim only with SDD400SFI**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)
	S9041TC/WH/SFI	240	10	850/1000/900	3000/4200/5700	90
	SDD400SFI	240	250			
	S9041BK RING					
	S9041SL RING					
	S9041SN RING					

Dimmable	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)
YES	80	WHITE	92	103	40(H)
YES		WHITE CAP			
		BLACK			
		SILVER			
		SATIN NICKEL			


Patent pending

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions



Dimensions



Photometric Data

Unit: cd C0/C180 — C30/C210 —
cd C60/C240 — C90/C270 —

S9041 TC at 3000K

