



LEEMAN MINI S9319 - 1.5W

LED 1.5 watt recessed MINI square profile and square cut-out wall luminaire

Application

Residential stairs, walkways and commercial features

Design Specifications

- Durable aluminium body profile
- White powder coat finish or anodised silver
- High efficiency SMD optics, CCT 3000K, beam distribution 86°
- Frosted glass diffuser
- Suitable drivers - PLUTO EGL12V/6W, PLUTO 15DV, 30DV, 50DV
- 12V AC or DC driver required, suitable drivers - PLUTO EGL12V/6W PLUTO 15DV, 40DV, 60DV



Performance

- Dimmable - **NO**




Technical Specification

Product	Model No.	Input Voltage (V/AC)	Input Voltage (V/DC)	Power (W)	Lumens (lm)	CCT (K)
	S9319 MW	12	12	1.5	70	3000
	S9319 AS	12	12	1.5	70	3000

CRI	Beam Angle (°)	Dimmable	Dim (mm)	Body Colour
80	86	NO	60(L) x 60(W) x 30(H)	White
80	86	NO	60(L) x 60(W) x 30(H)	Anodised Silver

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions



Photometric Data

Unit: cd C0/C180 — C90/C270 —

S9319 at 3000K

