





S-FIRE SELK1500SF2 - 4W

NON-MAINTAINED - SELK1500SF2 S-FIRE LED 4 watt emergency luminaire with adaptor ring

Application

A perfect choice for apartments or commercial spaces requiring compliance to AS/NZS 2293

Design Specifications

- Compliant to AS/NZS2293, with an impressive D63 emergency lighting classification, non-maintained
- Polycarbonate body profile, double insulation, Ø72mm cut-out and includes a Ø145mm adaptor ring (Max. Ø130mm cut-out)
- 4 watt system, LED charge status display and test switch, with remote control gear and high performance integral Lithium battery
- 1.2 m flex & 3 pin plug fitted, IC-4 rated (luminaire head only), trim colour white
- Guaranteed 90 minutes emergency function. Intelligent automatic recharging function, 16 hour recharge time and deep discharge protection
- Optional surface mount sheet metal box (only) SELK1500SF2SM/P available, dimensions L 220 x W 220 x H 60mm, colour white.









Performance

• Dimmable - NO



















Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	CCT (K)	CRI	Dim (mm)
To the second se	SELK1500SF2	240	4	6000	80	
	SELK1500SF2SM/P					220(L) × 220(W) × 60(H)





Mass (kg)

0.36

1

Important notes: (1) Battery warranty twelve (12) months (2) In the interest of transport and safety, emergency products are supplied with the battery disconnected. (3) In addition to specific emergency commissioning instructions, the battery MUST be connected at the time of installation. (4) Continual use in emergency mode greater than 240 hours without recharge, will result in battery failure and void battery warranty.

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions



