



MEMPHIS ROUND EMERGENCY SL9719RD/EM - 22W

MAINTAINED OR NON-MAINTAINED, vandal resistant, LED round profile, wall or ceiling mount luminaire, IK10, IP65

Application

A robust solution for industrial and commercial spaces

Design Specifications

- Die-cast aluminium body, frosted polycarbonate diffuser, silicone gasket, stainless steel allen screws
- Stainless steel allen screws
- High efficiency LED optics
- Integral non-dimmable LED driver
- Compliant to AS/NZS2293 Emergency Lighting & Exit Signs, guaranteed minimum 90 minutes emergency mode function with LiFePO4 battery technology
- Optional (non-dim) corridorSTANDBY function available, Emergency spacing - D32@C0



Performance

- Dimmable - **OPTIONAL**
- Dimmer Type - **TRAILING EDGE, 1-10V DALI / DSI**



Technical Specification


Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	SL9719RD/EM	240	22	1700	4000	80

Body Colour	Diameter (mm)	Dim (mm)
WHITE	316	102(H)

Important notes: (1) In the interest of transport and safety, emergency products are supplied with the battery disconnected. (2) In addition to specific emergency commissioning instructions, the battery **MUST** be connected at the time of installation. (3) Continual use in emergency mode greater than 240 hours without recharge, will result in battery failure and void battery warranty.

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions



Photometric Data

Photometric Data (at maintained power)

Unit: cd C0/C180 — C90/C270 —

