



ECOLINE EMERGENCY SL9732EM - 12/40W


MAINTAINED OR NON-MAINTAINED - Compliant to AS/NZS 2293, narrow body profile

Application



Perfect for interior commercial emergency lighting installations

Design Specifications

- Narrow steel body (65mm) body profile, white powder coat finish
- Designed with a large terminal block for easy installation
- LiFePO4 battery technology for long life
- Designed for both maintained and non-maintained systems
- High efficiency LED optics, selectable CCT 3000K/4000K/5700K, integral dual power selection, LED charge status display and test switch
- Guaranteed 90 minutes emergency function
corridorSTANDBY functions are optional for SL9732/40EM. Note: 20EM = D40C0, D25@C90, 40EM = D50@C0, D25@C90 emergency classification



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	CRI	Dim (mm)	Mass (kg)
	SL9732/20EM	240	20	80	600(L) x 65(W) x 65(H)	1.03
	SL9732/40EM	240	40	80	1135(L) x 65(W) x 65(H)	1.63

IPART	VEET
YES	YES
YES	YES


Important notes: (1) Battery warranty twelve (12) months (2) In the interest of transport and safety, emergency products are supplied with the battery disconnected. (3) In addition to specific emergency commissioning instructions, the battery **MUST** be connected at the time of installation. (4) Continual use in emergency mode greater than 240 hours without recharge, will result in

battery failure and void battery warranty.


Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

SL9732 40



SL9732 20




Photometric Data

Photometric Data (power on)

Unit: cd C0/C180 — C90/C270

SL9732/20EM at 5700K



SL9732/40EM at 5700K

