



## GLOW SL7362 - 4W

4 watt, IP67 LED inground luminaire, IK08 rated

### Application

Decorative residential exterior solution, ideal for decks and pathways

### Design Specifications

- Durable 304 stainless steel body
- Clear tempered glass diffuser
- Frosted optical LED lens
- High output LED optics, 12V DC constant voltage driver required
- Pre-wired 2 core rubber flex 1m with an IP67 nickel plated copper cable gland, PVC installation cannister included
- Suitable SAL LED drivers, PLUTO 15DV, PLUTO 40DV, PLUTO 60DV, IK08, IP67 performance



### Performance

- Dimmable - **NO**



### Technical Specification

| Product                                                                             | Model No.    | Input Voltage (V/DC) | Power (W) | Lumens (lm) | CCT (K) | CRI |
|-------------------------------------------------------------------------------------|--------------|----------------------|-----------|-------------|---------|-----|
|  | SL7362WW/SLS | 12                   | 4         | 300         | 3000    | 80  |
|  | SL7362DL/SLS | 12                   | 4         | 300         | 6000    | 80  |

| Beam Angle (°) | Mass (kg) | Dim (mm)      | Body Colour     |
|----------------|-----------|---------------|-----------------|
| 15             | 0.3       | 53(W) x 73(H) | STAINLESS STEEL |
| 15             | 0.3       | 53(W) x 73(H) | STAINLESS STEEL |

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

## Dimensions

SL7362

