



BLADE SL9709 TC - 25/50W

LED low profile batten with selectable colour temperature

Application

Conventional LED profile battens for commercial service spaces

Design Specifications

- Easy selectable colour temperature with an inbuilt DIP switch, 3000K, 4000K, 5700K
- Extruded aluminium body with plastic end cap with a rear cable channel allowing easy wiring
- Quality white powder coat finish
- Integral constant current non-dimmable LED driver, 25, 45 or 50 watt
- Robust opal polycarbonate diffuser
- High efficiency SMD LED chips, CRI >80, 120 degree beam



Technical Specification

Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI	Beam Angle (°)
SL9709/60TC	240	25	3400/3600/3600	3000/4000/5700	80	120
SL9709/120TC	240	45	6100/6500/6500	3000/4000/5700	80	120
SL9709/150TC	240	50	6900/7300/7300	3000/4000/5700	80	120

Model No.	Dim (mm)	Body Colour
SL9709/60TC	613(L) x 120(W) x 35(H)	WHITE
SL9709/120TC	1213(L) x 120(W) x 35(H)	WHITE
SL9709/150TC	1485(L) x 120(W) x 35(H)	WHITE

IMPORTANT, where CCT selection switching is provided, it is important to switch OFF the SUPPLY before the CCT selection is made, otherwise equipment damage may occur.

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

THE NEW ESS106 IS SMALL IN SIZE BUT BIG ON FEATURES.



For more
information
please
scan me

