PRODUCT DATASHEET
LED Value Batten 600 6 W 6500 K

LED VALUE BATTEN | LED batten luminaires

Areas of application

– Offices
– Residential interiors
– Hotels, restaurants, shops

Product benefits

– Mercury-free technology
– Value for money luminaire
– Accessories for flexible mounting options included

Product features

– Protection class: II
– Color rendering index R_a: ≥ 80
– Type of protection: IP20
– Lifetime: up to 15,000 h

TECHNICAL DATA

Electrical data

Nominal wattage	6.50 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	55.000 mA
Power factor λ	0.50
Protection class	II
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	650 lm
Luminous efficacy	100 lm/W
Color temperature	6500 K
Light color (designation)	Daylight
Color rendering index Ra	≥80
Standard deviation of color matching	≤7 sdcm
Beam angle	120 °

Dimensions & Weight

Length	585.00 mm
Width	22.20 mm
Height	32.50 mm
Product weight	76.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)|Polyvenyl
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+35 °C
Temperature range at storage	-20...+70 °C
Type of protection	IP20
Dimmable	No
Mounting location	Wall
Application environment	Indoor
LED module replaceable	Not replaceable

Lifespan

Number of switching cycles	15000

EQUIPMENT / ACCESSORIES

– External cable (1.5 m) and corner connection included

DOWNLOAD DATA

	DOWNLOAD DATA
	Tender documents
	IES file (IES)
	LDT file (Eulumdat)

	DOWNLOAD DATA
	UGR file (UGR table)

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075270527	Folding box 1	645 mm x 46 mm x 46 mm	153.00 g	1.36 dm³
4058075270534	Shipping box 20	660 mm x 200 mm x 245 mm	3787.00 g	32.34 dm³
4099854016585	Shipping box 20	660 mm x 200 mm x 245 mm	3787.00 g	32.34 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.