

# PRODUCT DATASHEET

## LED Value Batten 1200 13 W 4000 K

LED VALUE BATTEN | LED batten luminaires



---

### Areas of application

- Offices
- Residential interiors
- Hotels, restaurants, shops

---

### Product benefits

- Mercury-free technology
- Value for money luminaire
- Accessories for flexible mounting options included

---

### Product features

- Protection class: II
- Color rendering index  $R_a \geq 80$
- Type of protection: IP20
- Lifetime: up to 15,000 h




## TECHNICAL DATA

### Electrical data

Nominal wattage	13.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	110.000 mA
Power factor $\lambda$	0.50
Protection class	II
Operating mode	Integrated LED driver

### Photometrical data

Luminous flux	1300 lm
Luminous efficacy	100 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	$\geq 80$
Standard deviation of color matching	$\leq 7$ sdcM
Beam angle	120 °



### Dimensions & Weight

Length	1185.00 mm
Width	22.20 mm
Height	32.50 mm
Product weight	135.00 g



## Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC) Polyvenyl
Mercury content	0.0 mg

## Application & Mounting

Ambient temperature range	-20...+35 °C
Temperature range at storage	-20...+70 °C
Type of protection	IP20
Dimmable	No
Mounting location	Wall
Application environment	Indoor
LED module replaceable	Not replaceable




## Lifespan

Number of switching cycles	15000
----------------------------	-------

## EQUIPMENT / ACCESSORIES

- External cable (1.5 m) and corner connection included

## DOWNLOAD DATA

DOWNLOAD DATA	
	Tender documents
	IES file (IES)
	LDT file (Eulumdat)

## DOWNLOAD DATA



UGR file (UGR table)

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075270565	Folding box 1	1,245 mm x 46 mm x 46 mm	249.00 g	2.63 dm <sup>3</sup>
4058075270572	Shipping box 20	1,260 mm x 200 mm x 245 mm	6206.00 g	61.74 dm <sup>3</sup>
4099854016608	Shipping box 20	1,260 mm x 200 mm x 245 mm	6206.00 g	61.74 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.