

Cable tie Unity UV Resistant black 150 x 3.6 mm (x 1000)



Characteristics

Length (mm) : **150**
 Width (mm) : **3.6**
 Thickness (mm) : **1.2**
 Maximum clamping Ø (mm) : **35**
 Traction strength (N) : **178**
 Quantity per bag : **1000**

Norms

> EN 62275

Benefits

- These cable ties last 3-4 times longer than standard cable ties exposed to UV light.

Compliance marks



GENERAL INFORMATION

Technical details

Polyamide 6.6 with additive guaranteeing resistance to UV rays.
 Operating temperature (°C): -40 to +85.
 Installation temperature (°C): > = 0.
 Raw material flammability: UL94 V-2.
 Colour: black.
 Halogen free.

Application(s)

For attaching outdoor cables exposed to UV light.

LOGISTIC INFORMATION

Packaging



Zippable plastic bag with tear-off

Height (cm) : 13
 Length (cm) : 38
 Depth (cm) : 24
 Net weight (kg) : 0.72
 Gross weight (kg) : 0.74



Outer package 1



Carton box

Height (cm) : 23
 Length (cm) : 57
 Depth (cm) : 38
 Net weight (kg) : 12.98
 Gross weight (kg) : 15



x 18.00

Outer package 2



Pallet

Height (cm) : 107
 Length (cm) : 120
 Depth (cm) : 80
 Net weight (kg) : 240.02
 Gross weight (kg) : 256.02



x 288.00