

# Cable tie Unity UV Resistant black 100 x 2.5 mm (x 100)



## Characteristics

Length (mm) : **100**  
 Width (mm) : **2.5**  
 Thickness (mm) : **1.1**  
 Maximum clamping Ø (mm) : **22**  
 Traction strength (N) : **80**  
 Quantity per bag : **100**

## Norms

> EN 62275

## Benefits

- These cable ties last 3-4 times longer than standard cable ties exposed to UV light.

## Compliance marks



## GENERAL INFORMATION

### Technical details

Polyamide 6.6 with additive guaranteeing resistance to UV rays.  
 Operating temperature (°C): -40 to +85.  
 Installation temperature (°C): > = 0.  
 Raw material flammability: UL94 V-2.  
 Colour: black.  
 Halogen free.

### Application(s)

For attaching outdoor cables exposed to UV light.

## LOGISTIC INFORMATION

### Packaging



#### Zippable plastic bag with tear-off

Height (cm) : 2  
 Length (cm) : 20  
 Depth (cm) : 11  
 Net weight (kg) : 0.03  
 Gross weight (kg) : 0.03



### Outer package 1



#### Carton box

Height (cm) : 27  
 Length (cm) : 57  
 Depth (cm) : 38  
 Net weight (kg) : 12.06  
 Gross weight (kg) : 16.26

x 450.00



### Outer package 2



#### Pallet

Height (cm) : 123  
 Length (cm) : 120  
 Depth (cm) : 80  
 Net weight (kg) : 260.08  
 Gross weight (kg) : 276.08



x 7200.00