

Cable tie Unity UV Resistant black 300 x 4.8 mm (x 1000)



Characteristics

Length (mm) : **300**
 Width (mm) : **4.8**
 Thickness (mm) : **1.3**
 Maximum clamping Ø (mm) : **76**
 Traction strength (N) : **222**
 Quantity per bag : **1000**

Norms

> EN 62275

Benefits

- These cable ties last 3-4 times longer than standard cable ties exposed to UV light.

Compliance marks



GENERAL INFORMATION

Technical details

Polyamide 6.6 with additive guaranteeing resistance to UV rays.
 Operating temperature (°C): -40 to +85.
 Installation temperature (°C): > = 0.
 Raw material flammability: UL94 V-2.
 Colour: black.
 Halogen free.

Application(s)

For attaching outdoor cables exposed to UV light.

LOGISTIC INFORMATION

Packaging



Zippable plastic bag with tear-off

Height (cm) : 11
 Length (cm) : 48
 Depth (cm) : 35
 Net weight (kg) : 2.00
 Gross weight (kg) : 2.03



Outer package 1



Carton box

Height (cm) : 23
 Length (cm) : 57
 Depth (cm) : 38
 Net weight (kg) : 14.01
 Gross weight (kg) : 16.06



Outer package 2



Pallet

Height (cm) : 84
 Length (cm) : 120
 Depth (cm) : 80
 Net weight (kg) : 192.67
 Gross weight (kg) : 208.67

