

Cable tie Unity UV Resistant black 250 x 4.8 mm (x 1000)



Characteristics

Length (mm) : **250**
 Width (mm) : **4.8**
 Thickness (mm) : **1.35**
 Maximum clamping Ø (mm) : **60**
 Traction strength (N) : **222**
 Quantity per bag : **1000**

Norms

> EN 62275

Benefits

- These cable ties last 3-4 times longer than standard cable ties exposed to UV light.

Compliance marks



GENERAL INFORMATION

Technical details

Polyamide 6.6 with additive guaranteeing resistance to UV rays.
 Operating temperature (°C): -40 to +85.
 Installation temperature (°C): > = 0.
 Raw material flammability: UL94 V-2.
 Colour: black.
 Halogen free.

Application(s)

For attaching outdoor cables exposed to UV light.

LOGISTIC INFORMATION

Packaging



Zippable plastic bag with tear-off

Height (cm) : 11
 Length (cm) : 43
 Depth (cm) : 35
 Net weight (kg) : 1.75
 Gross weight (kg) : 1.77



Outer package 1



Carton box

Height (cm) : 33
 Length (cm) : 47
 Depth (cm) : 33
 Net weight (kg) : 15.71
 Gross weight (kg) : 18.07

x 9.00



Outer package 2



Pallet

Height (cm) : 114
 Length (cm) : 120
 Depth (cm) : 80
 Net weight (kg) : 271.04
 Gross weight (kg) : 287.04



x 135.00