

Cable tie Unity UV Resistant black 150 x 3.6 mm (x 100)



Characteristics

Length (mm): **150**
 Width (mm): **3.6**
 Thickness (mm): **1.2**
 Maximum clamping Ø (mm): **35**
 Traction strength (N): **178**
 Quantity per bag : **100**

Norms

> EN 62275

Benefits

- These cable ties last 3-4 times longer than standard cable ties exposed to UV light.

Compliance marks



GENERAL INFORMATION

Technical details

Polyamide 6.6 with additive guaranteeing resistance to UV rays.
 Operating temperature (°C): -40 to +85.
 Installation temperature (°C): > = 0.
 Raw material flammability: UL94 V-2.
 Colour: black.
 Halogen free.

Application(s)

For attaching outdoor cables exposed to UV light.

LOGISTIC INFORMATION

Packaging



Zippable plastic bag with tear-off

Height (cm) : 3
 Length (cm) : 27
 Depth (cm) : 11
 Net weight (kg) : 0.07
 Gross weight (kg) : 0.08



Outer package 1



Carton box

Height (cm) : 33
 Length (cm) : 47
 Depth (cm) : 33
 Net weight (kg) : 14.42
 Gross weight (kg) : 17.74

x 200.00



Outer package 2



Pallet

Height (cm) : 114
 Length (cm) : 120
 Depth (cm) : 80
 Net weight (kg) : 266.07
 Gross weight (kg) : 282.07



x 3000.00