

# Cable tie Unity UV Resistant black 778 x 9 mm (x 25)



## Characteristics

Length (mm) : **778**  
 Width (mm) : **9**  
 Thickness (mm) : **1.8**  
 Maximum clamping Ø (mm) : **228**  
 Traction strength (N) : **778**  
 Quantity per bag : **25**

## Norms

> EN 62275

## Benefits

- These cable ties last 3-4 times longer than standard cable ties exposed to UV light.

## Compliance marks



## GENERAL INFORMATION

### Technical details

Polyamide 6.6 with additive guaranteeing resistance to UV rays.  
 Operating temperature (°C): -40 to +85.  
 Installation temperature (°C): > = 0.  
 Raw material flammability: UL94 V-2.  
 Colour: black.  
 Halogen free.

### Application(s)

For attaching outdoor cables exposed to UV light.

## LOGISTIC INFORMATION

### Packaging



#### Polybag with colored label

Height (cm) : 4  
 Length (cm) : 95  
 Depth (cm) : 11  
 Net weight (kg) : 0.33  
 Gross weight (kg) : 0.35



3 700882 198921

### Outer package 1



#### Carton box

Height (cm) : 12  
 Length (cm) : 92  
 Depth (cm) : 34  
 Net weight (kg) : 13.11  
 Gross weight (kg) : 15.52



3 701395 100708

### Outer package 2



#### Pallet

Height (cm) : 111  
 Length (cm) : 120  
 Depth (cm) : 80  
 Net weight (kg) : 248.27  
 Gross weight (kg) : 264.27



3 701395 101033

x 640.00