

Cable tie Unity UV Resistant black 533 x 7.6 mm (x 25)



Characteristics

Length (mm) : **533**
 Width (mm) : **7.6**
 Thickness (mm) : **1.6**
 Maximum clamping Ø (mm) : **140**
 Traction strength (N) : **534**
 Quantity per bag : **25**

Norms

> EN 62275

Benefits

- These cable ties last 3-4 times longer than standard cable ties exposed to UV light.

Compliance marks



GENERAL INFORMATION

Technical details

Polyamide 6.6 with additive guaranteeing resistance to UV rays.
 Operating temperature (°C): -40 to +85.
 Installation temperature (°C): > = 0.
 Raw material flammability: UL94 V-2.
 Colour: black.
 Halogen free.

Application(s)

For attaching outdoor cables exposed to UV light.

LOGISTIC INFORMATION

Packaging



Polybag with colored label

Height (cm) : 3
 Length (cm) : 68
 Depth (cm) : 11
 Net weight (kg) : 0.19
 Gross weight (kg) : 0.20



Outer package 1



Carton box

Height (cm) : 23
 Length (cm) : 57
 Depth (cm) : 38
 Net weight (kg) : 12.3
 Gross weight (kg) : 14.14



Outer package 2



Pallet

Height (cm) : 107
 Length (cm) : 120
 Depth (cm) : 80
 Net weight (kg) : 226.23
 Gross weight (kg) : 242.23



x 1040.00