

## Hornet LED Floodlight

### CFL20840

- Cool white (4000K) is ideal for commercial or general lighting application
- Adjustable head 300° horizontal, 200° vertical with flexibility to direct the light (up/down/sideways)
- Retro-fit accessory included for easy installation onto existing floodlight mounting points



#### Performance

System Power	20W
Exit Lumen	1600lm
Efficacy	80lm/W
CCT	4000K
CRI	80
Operating Temperature	0°C to 40°C
MacAdam Steps	7SDCM
Ingress Protection Rating	IP66
Impact Rating	IK07
Beam Distribution	Symmetric
Beam Angle	120°
Warranty	3 Years
Lifetime	30,000hrs (L70/B50)


#### Physical

Dimensions	L187 x W125 x H23mm
Diffuser	Polycarbonate
Luminaire Colour	Black
Weight	0.42kg
Luminaire Material	Aluminium (Die Cast)
Driver Location	Integrated
Heatsink	Aluminium (Die Cast)
Finish	Powder Coated
Installation	Surface Mounting


#### Electrical

Dimming	Non - Dimmable
Voltage	240V
Inrush Current	10A
Inrush Current Duration	200µs
Line Current	0.12A
Electrical Rating	Class I

#### Line Drawings



#### Photometrics



#### Product Images



