



## 2P 63A Switch , Red Toggle

SBR264

### Architecture

Type of order	Break switch
Neutral position	without neutral
Number of poles	2 P
Type of pole	2 P

### Main electrical features

Frequency	50/60 Hz
Rated operational voltage Ue	400 V

### Voltage

Rated insulation voltage	440 V
Type of voltage input 1	AC
Rated impulse withstand voltage	6000 V

### Electric current

Rated operational current in AC21 category A	63 A
Rated operational current in AC21 category B	63 A
Acceptable current rating with AC22 category A	63 A
Acceptable current rating with AC22 category B	63 A
Rated current	63 A
Rated short-circuit making capacity Icm under 415V AC according IEC 60947-3	1332 A
Rated short-time withstand current 1s	0,945 kA
Thermal rated current outside of housings	63 A

### Power

Power loss per pole at In	2,2 W
Total power loss under IN	4,4 W

### Endurance

Electrical durability at nominal load in AC21 in operating cycles	2500
Electrical durability at nominal load in AC22 in operating cycles	2500
Number of mechanical operations	40000

#### Dimensions

Depth of installed product	68 mm
Height of installed product	83 mm
Width of installed product	35 mm

#### Installation, mounting

Tightening torque	3,6Nm
Bottom removability for modular devices	yes
Top removability for modular devices	no

#### Connection

Cage clamp position	in line
Connection cross-sect. rigid cable	6 / 50mm <sup>2</sup>
Connection cross-sect. flexible conductor	6 / 35mm <sup>2</sup>
Type of connection	with screw

#### Equipment

Quantity of NO contacts	2
Can be accessorized	yes

#### Standards

Standard text	IEC 60947-3
European directive WEEE	not concerned

#### Safety

Protection index IP	IP20
---------------------	------

#### Use conditions

Degree of pollution according to IEC 60664 / IEC 60947-2	2
Operating temperature	-20 50 °C
Altitude	2000 m
Storage/transport temperature	-40 80 °C