

PRODUCT DATASHEET LED Value Weatherproof Batten 1200 20/40W TRI

LEDVALUE IP65 POWER AND CCT CHANGE WEATHERPROOF BATTEN | Weatherproof batten family with high IP rating and CCT and power change



AREAS OF APPLICATION

- Car parks and underpasses
- Garages
- Industrial and storage facilities

PRODUCT BENEFITS

- Homogeneous light output
- High-power LED for high light output

PRODUCT FEATURES

- Average lifespan: 50,000 h
- Type of protection: IP65
- 6 mm terminal block for easy installation



TECHNICAL DATA

Electrical data

Nominal wattage	40.00 W
Operating mode	Integrated LED driver
Nominal voltage	220240 V
Power factor λ	0.90
Mains frequency	50/60 Hz
Total harmonic distortion	< 25 %

Photometrical data

Luminous efficacy	100 lm/W	
Standard deviation of color matching	6 sdcm	
Color rendering index Ra	80	

Light technical data

Beam angle	115 °

Dimensions & weight

Length	1200 mm
Width	96.0 mm
Height	79.0 mm
Product weight	1520.00 g

Colors & materials

Body material	Polycarbonate (PC)
Product color	Blue/gray
Housing color	Blue/gray
Cover material	Polycarbonate (PC)

Lifespan

Number of switching cycles	100000
Lifespan L70/B50 at 25 °C	50000 h

Additional product data

Mounting type	Surface
Mounting location	Ceiling

Capabilities

Dimmable	No
Type of connection	Terminal

LED module replaceable Not replaceable

Certificates & standards

Protection class IK (shock resistance)	IK08
Protection class	I
Type of protection	IP65

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075393547	Folding carton box 1	1205 mm x 100 mm x 83 mm	1730.00 g	10.00 dm ³
4058075393554	Shipping carton box 6	1219 mm x 178 mm x 244 mm	11249.00 g	52.94 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.