

PRODUCT DATASHEET

LED Value Weatherproof Batten 42 W 4000 K EM

LED VALUE WEATHERPROOF BATTEN EMERGENCY | Weatherproof batten family with a wide range of wattage, sizes and emergency lighting function



Areas of application

- Car parks and underpasses
- Garages

Product benefits

- Homogeneous light output
- High-power LED for high light output

Product features

- Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Average lifespan: 50,000 h
- Type of protection: IP65



TECHNICAL DATA

Electrical data

Nominal wattage	42.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	202.000 mA
Power factor λ	0.90
Total harmonic distortion	< 25 %
Protection class	I
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	4200 lm
Luminous efficacy	100 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	80
Standard deviation of color matching	6 sdcn
Beam angle	112 °

Dimensions & Weight

Length	1265.00 mm
Width	130.00 mm
Height	92.00 mm
Product weight	2350.00 g

Materials & Colors

Product color	Gray/White
Housing color	Gray/White
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Type of connection	Screw terminal
Type of protection	IP65

Protection class IK (shock resistance)	IK08
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling
LED module replaceable	Not replaceable

Lifespan

Lifespan L70/B50 at 25 °C	30000 h
---------------------------	---------

DOWNLOAD DATA

DOWNLOAD DATA



Tender documents



IES file (IES)

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075396586	Folding box 1	1,267 mm x 130 mm x 93 mm	2677.00 g	15.32 dm ³
4058075396593	Shipping box 6	1,281 mm x 274 mm x 304 mm	17385.00 g	106.70 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.