

PRODUCT FAMILY DATASHEET

LED VALUE WEATHERPROOF BATTEN EMERGENCY

Weatherproof batten family with a wide range of wattage, sizes and emergency lighting function

AREAS OF APPLICATION

- Car parks and underpasses
- Garages



PRODUCT BENEFITS

- Homogeneous light output
- High-power LED for high light output

PRODUCT FEATURES

- Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Average lifespan: 50,000 h
- Type of protection: IP65



TECHNICAL DATA

Product description	Electrical data			Photometrical data				Light technical data	Dimensions & weight			
	Nominal wattage	Nominal voltage	Mains frequency	Color temperature	Luminous flux	Light color (designation)	Color rendering index Ra	Beam angle	Length	Width	Height	Product weight
LED Value Weatherproof Batten 22 W 3000 K EM	22.00 W	220...240 V	50/60 Hz	3000 K	2200 lm	Warm White	80	115 °	1199 mm	77.0 mm	68.0 mm	1510.00 g
LED Value Weatherproof Batten 22 W 4000 K EM	22.00 W	220...240 V	50/60 Hz	4000 K	2420 lm	Cool White	80	115 °	1199 mm	77.0 mm	68.0 mm	1510.00 g
LED Value Weatherproof Batten 22 W 6500 K EM	22.00 W	220...240 V	50/60 Hz	6500 K	2420 lm	Cool Daylight	80	115 °	1199 mm	77.0 mm	68.0 mm	1510.00 g
LED Value Weatherproof Batten 42 W 3000 K EM	42.00 W	220...240 V	50/60 Hz	3000 K	4400 lm	Warm White	80	115 °	1199 mm	77.0 mm	68.0 mm	1570.00 g
LED Value Weatherproof Batten 42 W 4000 K EM	42.00 W	220...240 V	50/60 Hz	4000 K	4800 lm	Cool White	80	115 °	1199 mm	77.0 mm	68.0 mm	1570.00 g
LED Value Weatherproof Batten 42 W 6500 K EM	42.00 W	220...240 V	50/60 Hz	6500 K	4800 lm	Cool Daylight	80	115 °	1199 mm	77.0 mm	68.0 mm	1570.00 g
LED Value Weatherproof Batten 27 W 3000 K EM	27.00 W	220...240 V	50/60 Hz	3000 K	2750 lm	Warm White	80	115 °	1499 mm	77.0 mm	68.0 mm	1780.00 g
LED Value Weatherproof Batten 27 W 4000 K EM	27.00 W	220...240 V	50/60 Hz	4000 K	3000 lm	Cool White	80	115 °	1499 mm	77.0 mm	68.0 mm	1780.00 g
LED Value Weatherproof Batten 27 W 6500 K EM	27.00 W	220...240 V	50/60 Hz	6500 K	3000 lm	Cool Daylight	80	115 °	1499 mm	77.0 mm	68.0 mm	1780.00 g
LED Value Weatherproof Batten 52 W 3000 K EM	52.00 W	220...240 V	50/60 Hz	3000 K	5500 lm	Warm White	80	115 °	1499 mm	77.0 mm	68.0 mm	1860.00 g
LED Value Weatherproof Batten 52 W 4000 K EM	52.00 W	220...240 V	50/60 Hz	4000 K	6000 lm	Cool White	80	115 °	1499 mm	77.0 mm	68.0 mm	1860.00 g
LED Value Weatherproof Batten 52 W 6500 K EM	52.00 W	220...240 V	50/60 Hz	6500 K	6000 lm	Cool Daylight	80	115 °	1499 mm	77.0 mm	68.0 mm	1860.00 g
LED Value Weatherproof Batten 22 W 4000 K EM	22.00 W	220...240 V	50/60 Hz	4000 K	2200 lm	Cool White	80	112 °	1265 mm	130.0 mm	92.0 mm	2280.00 g
LED Value Weatherproof Batten 42 W 4000 K EM	42.00 W	220...240 V	50/60 Hz	4000 K	4200 lm	Cool White	80	112 °	1265 mm	130.0 mm	92.0 mm	2350.00 g

Product description	Electrical data			Photometrical data				Light technical data	Dimensions & weight			
	Nominal wattage	Nominal voltage	Mains frequency	Color temperature	Luminous flux	Light color (designation)	Color rendering index Ra	Beam angle	Length	Width	Height	Product weight
LED Value Weatherproof Batten 52 W 4000 K EM	52.00 W	220...240 V	50/60 Hz	4000 K	5200 lm	Cool White	80	112 °	1265 mm	130.0 mm	92.0 mm	3020.00 g

Product description	Colors & materials				Temperatures & operating conditions	Lifespan	Capabilities	
	Body material	Housing color	Product color	Cover material	Ambient temperature range	Lifespan L70/B50 at 25 °C	Dimmable	Type of connection
LED Value Weatherproof Batten 22 W 3000 K EM	Aluminum/Polycarbonate (PC)	BLUE/GRAY	BLUE/GRAY	Polycarbonate (PC)	0...+40 °C	30000 h	No	Terminal
LED Value Weatherproof Batten 22 W 4000 K EM	Aluminum/Polycarbonate (PC)	BLUE/GRAY	BLUE/GRAY	Polycarbonate (PC)	0...+40 °C	30000 h	No	Terminal
LED Value Weatherproof Batten 22 W 6500 K EM	Aluminum/Polycarbonate (PC)	BLUE/GRAY	BLUE/GRAY	Polycarbonate (PC)	0...+40 °C	30000 h	No	Terminal
LED Value Weatherproof Batten 42 W 3000 K EM	Aluminum/Polycarbonate (PC)	BLUE/GRAY	BLUE/GRAY	Polycarbonate (PC)	0...+40 °C	30000 h	No	Terminal
LED Value Weatherproof Batten 42 W 4000 K EM	Aluminum/Polycarbonate (PC)	BLUE/GRAY	BLUE/GRAY	Polycarbonate (PC)	0...+40 °C	30000 h	No	Terminal
LED Value Weatherproof Batten 42 W 6500 K EM	Aluminum/Polycarbonate (PC)	BLUE/GRAY	BLUE/GRAY	Polycarbonate (PC)	0...+40 °C	30000 h	No	Terminal
LED Value Weatherproof Batten 27 W 3000 K EM	Aluminum/Polycarbonate (PC)	BLUE/GRAY	BLUE/GRAY	Polycarbonate (PC)	0...+40 °C	30000 h	No	Terminal
LED Value Weatherproof Batten 27 W 4000 K EM	Aluminum/Polycarbonate (PC)	BLUE/GRAY	BLUE/GRAY	Polycarbonate (PC)	0...+40 °C	30000 h	No	Terminal
LED Value Weatherproof Batten 27 W 6500 K EM	Aluminum/Polycarbonate (PC)	BLUE/GRAY	BLUE/GRAY	Polycarbonate (PC)	0...+40 °C	30000 h	No	Terminal
LED Value Weatherproof Batten 52 W 3000 K EM	Aluminum/Polycarbonate (PC)	BLUE/GRAY	BLUE/GRAY	Polycarbonate (PC)	0...+40 °C	30000 h	No	Terminal
LED Value Weatherproof Batten 52 W 4000 K EM	Aluminum/Polycarbonate (PC)	BLUE/GRAY	BLUE/GRAY	Polycarbonate (PC)	0...+40 °C	30000 h	No	Terminal

Product description	Colors & materials				Temperatures & operating conditions	Lifespan	Capabilities	
	Body material	Housing color	Product color	Cover material	Ambient temperature range	Lifespan L70/B50 at 25 °C	Dimmable	Type of connection
LED Value Weatherproof Batten 52 W 6500 K EM	Aluminum/Polycarbonate (PC)	BLUE/GRAY	BLUE/GRAY	Polycarbonate (PC)	0...+40 °C	30000 h	No	Terminal
LED Value Weatherproof Batten 22 W 4000 K EM	Polycarbonate (PC)	Gray/White	Gray/White	Polycarbonate (PC)		30000 h	No	Screw terminal
LED Value Weatherproof Batten 42 W 4000 K EM	Polycarbonate (PC)	Gray/White	Gray/White	Polycarbonate (PC)		30000 h	No	Screw terminal
LED Value Weatherproof Batten 52 W 4000 K EM	Polycarbonate (PC)	Gray/White	Gray/White	Polycarbonate (PC)		30000 h	No	Screw terminal

Product description	Certificates & standards	
	Protection class	Type of protection
LED Value Weatherproof Batten 22 W 3000 K EM	I	IP65
LED Value Weatherproof Batten 22 W 4000 K EM	I	IP65
LED Value Weatherproof Batten 22 W 6500 K EM	I	IP65
LED Value Weatherproof Batten 42 W 3000 K EM	I	IP65
LED Value Weatherproof Batten 42 W 4000 K EM	I	IP65
LED Value Weatherproof Batten 42 W 6500 K EM	I	IP65
LED Value Weatherproof Batten 27 W 3000 K EM	I	IP65
LED Value Weatherproof Batten 27 W 4000 K EM	I	IP65
LED Value Weatherproof Batten 27 W 6500 K EM	I	IP65
LED Value Weatherproof Batten 52 W 3000 K EM	I	IP65

Product description	Certificates & standards	
	Protection class	Type of protection
LED Value Weatherproof Batten 52 W 4000 K EM	I	IP65
LED Value Weatherproof Batten 52 W 6500 K EM	I	IP65
LED Value Weatherproof Batten 22 W 4000 K EM	I	IP65
LED Value Weatherproof Batten 42 W 4000 K EM	I	IP65
LED Value Weatherproof Batten 52 W 4000 K EM	I	IP65

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075396098	Shipping carton box 6	1219 mm x 178 mm x 244 mm	11189.00 g	52.94 dm ³
4058075396128	Shipping carton box 6	1219 mm x 178 mm x 244 mm	11189.00 g	52.94 dm ³
4058075396142	Shipping carton box 6	1219 mm x 178 mm x 244 mm	11189.00 g	52.94 dm ³
4058075396166	Shipping carton box 6	1219 mm x 178 mm x 244 mm	11549.00 g	52.94 dm ³
4058075396180	Shipping carton box 6	1219 mm x 178 mm x 244 mm	11549.00 g	52.94 dm ³
4058075396203	Shipping carton box 6	1219 mm x 178 mm x 244 mm	11549.00 g	52.94 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075396227	Shipping carton box 6	1519 mm x 178 mm x 244 mm	13289.00 g	65.97 dm ³
4058075396241	Shipping carton box 6	1519 mm x 178 mm x 244 mm	13289.00 g	65.97 dm ³
4058075396265	Shipping carton box 6	1519 mm x 178 mm x 244 mm	13289.00 g	65.97 dm ³
4058075396289	Shipping carton box 6	1519 mm x 178 mm x 244 mm	13769.00 g	65.97 dm ³
4058075396302	Shipping carton box 6	1519 mm x 178 mm x 244 mm	13769.00 g	65.97 dm ³
4058075396326	Shipping carton box 6	1519 mm x 178 mm x 244 mm	13769.00 g	65.97 dm ³
4058075396579	Shipping carton box 6	1281 mm x 274 mm x 304 mm	16965.00 g	106.70 dm ³
4058075396593	Shipping carton box 6	1281 mm x 274 mm x 304 mm	17385.00 g	106.70 dm ³
4058075396616	Shipping carton box 4	1581 mm x 274 mm x 189 mm	15391.00 g	81.87 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.