



Pan-Lug™ LCD10-14A-L Comp. Lug, Tin Plt Cu, Two 1/4" Stud, 0.63" Spacing, PK50

LCD10-14A-L

The LCD10-14A-L Tin-Plated Copper Compression Connector Lug, two-hole, standard barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. The long barrel maximizes the number of crimps and provides premium wire pull-out strength and performance. An inspection window aids to visually assure full conductor insertion, and the tin-plate material helps to inhibit corrosion. UL Listed and CSA Certified.

Specifications

Product Type	Compression Lug
Base Material	Copper
Number of Stud Holes	2
Barrel Type	Standard
Barrel Entry	Beveled
Tongue Type	Standard
Tongue Angle	Straight
Inspection Window	Yes
Finish/Coating	Tin-Plated
Stud Hole Size (In.)	1/4
Stud Hole Size (mm)	6.4
Stud Hole Spacing (In.)	0.63
Stud Hole Spacing (mm)	16
Copper Code Conductor Size (AWG)	10
Barrel Length (In.)	0.38
Barrel Length (mm)	9.7
Tongue Width (In.)	0.42
Tongue Width (mm)	10.7
Tongue Thickness (In.)	0.05
Tongue Thickness (mm)	1.3
Overall Length (In.)	1.78
Overall Length (mm)	45.3
Standards Met	CSA certified C22.2 No. 65-13, UL Listed to 486A-486B File #E52164, NEBS Level 3
CSA Temperature Rating (°C)	90
UL Temperature Rating (°C)	90

Specifications (continued)

Maximum Voltage (kV)	35
Wire Strip Length (In.)	7/16
Wire Strip Length (mm)	11.1
Note	Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 V
Sub Brand	Pan-Lug™
Part Features	Tin plated to inhibit corrosion,color coded barrel,inspection window, NEBS level 3.

Packaging Detail

UPC	07498397234
Std. Pkg. Qty.	50
Std. Pkg. Volume (cf)	0.0105
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000