



Pan-Ty® PLT4H-L86 Cable Tie, Light Blue, Met Det PA6.6, 14.4"L, 120lb, PK50

PLT4H-L86

Panduit PLT4H-L86 Locking Cable Ties are designed to help the food, beverage and pharmaceutical industries meet product manufacturing safety standards. Featuring metal impregnated material, these metal detectable products are identifiable by metal detection equipment. Additionally, the distinct color facilitates quick visual detection. Light-Heavy cross section, 14.4" (282mm) length. Made of Metal Detectable Nylon 6.6., are light blue in color and come in packages of 50.

 **Discontinued - Limited Stock**

Suggested Replacement Parts: PLT4H-L96A

Note: It is the buyer's responsibility to determine if the suggested replacement part is suitable for your application and intended use.

Specifications

Material Description	Nylon 6.6 ()
Product Type	Premium Cable Tie
Color	Light Blue
Environment	Indoor
Material	Nylon 6.6
Material Properties	Metal-Impregnated
Overall Length (In.)	14.4
Overall Length (mm)	366
Body Width (In.)	0.3
Body Width (mm)	7.6
Body Thickness (In.)	0.075
Body Thickness (mm)	1.9
Maximum Bundle Diameter (In.)	4
Maximum Bundle Diameter (mm)	102
Minimum Bundle Diameter (In.)	0.25
Minimum Bundle Diameter (mm)	6.4
Minimum Loop Tensile Strength (N)	534
Minimum Loop Tensile Strength (lb)	120
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185

Specifications (continued)

Minimum Operating Temperature (°C)	-40
Minimum Operating Temperature (°F)	-40
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	RoHS Compliant
For Use With	GTH-E, GS4H-E, GS4EH-E, STH2, ST3EH
Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.

Packaging Detail

UPC	07498303007
Std. Pkg. Qty.	50
Std. Pkg. Volume (cf)	0.0534
Std. Ctn. Qty.	500
Std. Ctn. Volume (cf)	0.5339