


FEATURED



45° Angled Wire Cap for Cat 6A UTP TG Jack

CJLRCAPBU-X

Angled TG wire cap, Cat. 6A, 10 pk., blue

Specifications

Product Type	Wire Cap
Performance Level	Category 6A
Connector Type	Jack Accessory
Termination Style	TG Style
Body Material	Polycarbonate
Module Type	Mini-Com®
Wiring Scheme	T568A/T568B
Shield Type	Unshielded (UTP)
Sub Brand	Pan-Net®
Maximum Operating Temperature (°C)	75
Maximum Operating Temperature (°F)	167
Minimum Operating Temperature (°C)	-10
Minimum Operating Temperature (°F)	14
Maximum Storage Temperature (°C)	75
Maximum Storage Temperature (°F)	167
Minimum Storage Temperature (°C)	-40
Minimum Storage Temperature (°F)	-40
Color	Blue
Standards Met	Exceeds Channel and Component Requirements of ANSI/TIA-568-C.2 and ISO 11801 Standards for the Respective Category, Meets IEC 60603-7, Supports 2500 Connection Cycles with IEEE 802.3af / 802.3at and proposed 802.3bt Type 3 and Type 4, UL 1863 and UL 2043 and RoHS Compliant
Overall Length (In.)	0.96
Overall Length (mm)	24.4
Overall Width (In.)	0.61
Overall Width (mm)	15.5
Overall Depth (In.)	0.96
Overall Depth (mm)	24.4
Overall Height (In.)	0.63
Overall Height (mm)	16

Packaging Detail

UPC	61305625633
Std. Pkg. Qty.	10
Std. Pkg. Volume (cf)	0.0077
Std. Ctn. Qty.	100
Std. Ctn. Volume (cf)	0.0771