

FEATURED



OptiCam® SC Simplex Connector, OM3/OM4/OM5, Aqua

FSC2MCXAQ

The OptiCam® SC Fiber Optic Connector is a multimode 50/125µm OM3/OM4/OM5 simplex fiber connector, intended for 900-micron tight-buffered fiber installation. Field termination can be done in about two minutes using the OptiCam 2 Termination Tool. The pre-polished fiber endface eliminates time-consuming field polishing, reducing installation costs. The SC connector has a natural-colored body with an aqua-colored backbone, outer housing, and 900µm boot.

Specifications

Note	For use with the OptiCam 2 Termination Tool
Polish Type	Pre-Polished
Fiber Type	OM3/OM4/OM5
Connection Type	SC
Sub Brand	OptiCam®
Application	Maintenance or emergency restoration of fiber networks and retrofit/initial install in both behind-the-wall (BTW) and in the permanent side of panelized interconnect and cross-connect.
Body Style	Simplex
Color	Aqua
Boot Color	Aqua
Backbone Color	Natural
Fiber Diameter (µm)	900
Maximum Operating Temperature (°C)	60
Maximum Operating Temperature (°F)	140
Minimum Operating Temperature (°C)	0
Minimum Operating Temperature (°F)	32
Standards Met	RoHS Compliant; TIA/EIA-604 FOCIS-3 compliant; exceeds TIA/EIA-568-D.3 requirements
Product Type	Fiber Optic Connector

Packaging Detail

UPC	61305625636
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.0032
Std. Ctn. Qty.	10
Std. Ctn. Volume (cf)	0.0324