



Mini-Com® RJ45 Cat 6A Shuttered TG Jack Module, BU

CJH6X88TGBU

The Mini-Com® Cat 6A UTP RJ45 Spring-Shuttered TG Jack Module is designed to terminate 4-pair, 22-26 AWG twisted pair cable. Each module is 100% factory tested to exceed industry standard performance requirements. The integrated spring-shuttered door keeps dust and debris out of unmated RJ45 jack modules. Each jack is individually serialized for traceability and is compatible with Mini-Com Modular Patch Panels and Faceplates. The jack module is blue.

Specifications

Product Type	Jack Module
Performance Level	Category 6A
Connector Type	Jack Module - Shuttered
Termination Style	TG Style
Body Material	Polycarbonate
Contact Material	Plated Phosphor Bronze
Module Type	Mini-Com®
Wiring Scheme	T568A/T568B
Shield Type	Unshielded (UTP)
Sub Brand	Pan-Net®
Maximum Operating Temperature (°C)	75
Maximum Operating Temperature (°F)	167
Minimum Operating Temperature (°C)	-10
Minimum Operating Temperature (°F)	14
Maximum Storage Temperature (°C)	75
Maximum Storage Temperature (°F)	167
Minimum Storage Temperature (°C)	-40
Minimum Storage Temperature (°F)	-40
Resistance Properties	Heat-Resistant
Color	Blue
Standards Met	Exceeds Channel and Component Requirements of ANSI/TIA-568-C.2 Category 5e and ISO 11801 Class D Standards at Swept Frequencies 1 to 100 MHz, Meets ANSI/TIA-1096-A, Meets IEC 60603-7, Rated for 2500 Cycles with IEEE 802.3af / 802.3at and Proposed 802.3bt Type 3 and Type 4, UL 1863 and UL 2043 and RoHS Compliant
Overall Length (In.)	1.5

Specifications (continued)

Overall Length (mm)	38.1
Overall Width (In.)	0.63
Overall Width (mm)	16
Overall Depth (In.)	1.5
Overall Depth (mm)	38.1
Overall Height (In.)	0.71
Overall Height (mm)	18

Packaging Detail

UPC	61305601494
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.0032
Std. Ctn. Qty.	50
Std. Ctn. Volume (cf)	0.1605