Rechargeable LED handlamp and wireless speaker

A portable lamp with connected speaker.





Benefits

• A strong and powerful wireless speaker.

Norms > IP 54, IK 7

3 1

Compliance marks

UK CA

GENERAL INFORMATION

Description

Rechargeable LED hand lamp with wireless speaker.

Technical details

Power: 5 W + 1 W.

Luminescent flux: 500 Lm at 50 Lm (wide beam) or 250Lm (spot beam).

Colour temperature: 6000 K.

Colour rendering index: ≥ 80.

Beam angle: Wide (120 °) and Spot (40 °).

Material: PC and aluminum.

Magnetic hook and swivel 180°.

Autonomy: from 2.5 h to 7 h.

Charging time: 4.5 h.

Load indicator.

Operating temperature: -20° C to + 45° C.

Wireless connection with a range of 10 m.

Output power of the wireless speaker: 5 W.

Autonomy of the speaker: 7 h.

Lithium battery: 3.7 V 3000 mAh.

Supplied with a USB / micro-USB connection cable 1m long.

Weight: 0.33 Kg.

Advice

Keep the speaker button pressed for 3 seconds to activate its function. Once activated, pair your smartphone with the lamp. It responds with a sound. Play the music. Adjust the sound from your smartphone. To turn off this function, keep the speaker button pressed for 3 seconds. Fully charge and discharge the battery for a better service life. The product operates when connected to the mains.

Application(s)

Battery-powered inspection lighting.

Instructions

- 1. Press once: wide beam on at 50%
- 2. Press twice: wide beam on 100%
- 3. Press continuously: the luminous flux varies gradually from 10% to 100%
- 4. Press three times: spot beam on.



LOGISTIC INFORMATION

Packaging



Carton box

Height (cm): 17 Length (cm): 7 Depth (cm): 5

- Net weight (kg): 0.34 Gross weight (kg): 0.37



Outer package 1



Carton box

Height (cm): 21 **Length (cm): 22 Depth (cm): 18** Net weight (kg): 4.4



Gross weight (kg): 4.6 Outer package 3

Outer package 2



Carton box

Height (cm): 23 Length (cm): 37.5 **Depth (cm):** 23.5 Net weight (kg): 9.2



Pallet



Height (cm): 100 **Length (cm):** 120 Depth (cm): 80
Net weight (kg): 384



