





CALEO

CALEO30W-5K

SAP CODE: 2000697



Photometric Diagram



Unit: cd
 - C0/180 110.0deg
 - C90/270 110.0deg

30W, wall mounted security/safety LED light

A practical and sturdy vandal resistant outdoor fixture.

KEY INFORMATION

Lumen Output	2290lm
Input Power	30W
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	Non-Dimmable
Trim Colour	BLACK
Warranty	3yr
IP Rating	IP65
IK Rating	IK08
IC Rating	N/A
Rebate Scheme Approvals	N/A

PHOTOMETRIC

Efficacy	76lm/W
LED	SMD
CCT	5000K
CRI	>70
Beam Angle	110°

ELECTRICAL

Driver	Integral
Supply Input	220-240V, 50/60Hz
Driver Output Voltage	22VDC
Power Factor	>0.9
LED Input Current (nominal)	350mA
Useful life @Ta25° (L70)	50,000hr

CONSTRUCTION

Housing	Aluminium
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	N/A
Connection Type	Terminal Block PA14
Total Weight	2.15kg
Dimensions	308x288x120mm
Operating Ambient Temp.	-20 to 50°C
Electrical Classification	Class 1