


FLEXION RGB 5M KIT

FS40W5MRGB30-IP54

SAP CODE: 2001480



RGB, IP54, 40W, 5m flexible, trimmable LED strip


An RGB strip with remote control for intensity, colour and sequence.

Accessories

DIMMABLE DRIVER



Photometric Diagram



Unit: cd
- C0/180 125.0deg
- C90/180 125.0deg

KEY INFORMATION

Lumen Output	R: 290lm G: 560lm B: 160lm RGB: 975lm
Input Power	40W
Dimming Options	*Phase-Cut Dimming
Trim Colour	WHITE
Warranty	5yr
IP Rating	IP54
Rebate Scheme Approvals	N/A

PHOTOMETRIC

LED	SMD
Efficacy	24.4lm/W
CCT	RGB
Beam Angle	120°

ELECTRICAL

Driver	Remote
Supply Input	220-240V, 50/60Hz
Driver Output Voltage	24VDC
Power Factor	>0.9
LED Input Current (nominal)	2800mA
Useful life @Ta25° (L70)	50,000hr

CONSTRUCTION

Fixings/Hardware	Self Adhesive Backing & Saddles
Connection Type	1.2m Flex & Plug
Total Weight	0.5kg
Dimensions	5000 x 10 x 2mm
Operating Ambient Temp.	-30 to 55°C
Electrical Classification	Class 2
Cut Length	167mm

*Dimming performance may vary depending on the specifications of the dimmer being used. For best performance use the Haneco DUO-350W dimmer.