Catalogue No: **CA9-146-11-480W-KIT**

KIT CONTACTOR 75kW 3P 250-500V AC/DC COIL 1NO 1NC AUX

Motor Control and Drives > Motor Starting and Protection > Contactors > Sprecher + Schuh Contactors > CA9 Contactors 55 to 630kW > 3 Pole Contactors with AC/DC Coil





Representative Photo Only (actual product may vary based on configuration selections)

- Simplifies selection with electronic wide-range AC/DC coils
- Available integrated PLC interface
- Saves energy with low power consumption
- Includes built-in surge suppression
- For ease of change over, adaptor plates available in KIT form for CA6 to CA9 migration

SPECIFICATIONS	
Product Series	CA9
Component Type Motor Control and Drives	Standard Contactor
le, Rated Operational Current, AC-1, 690V, 40°C	225 A@690V,40°C
le, Rated Operational Current, AC-1, 1kV, 40°C	225 A@1kV,40°C
kW Rating, AC-3, 415V, 60°C	75 kW @415V, 60°C
le, Rated Operational Current, AC-3, 415V, 60°C	146 A@415V,60°C
kW Rating, AC-3, 690V, 60°C	90 kW @690V, 60°C
le, Rated Operational Current, AC-3, 690V, 60°C	93 A@690V,60°C
kW Rating, AC-3, 1kV, 60°C	75 kW @1kV, 60°C
le, Rated Operational Current, AC-3, 1000V, 60°C	60 A@1000V,60°C
Coil Type	Electronic type
REFERENCES	
IECEx Certificate -	
Supplier Declaration of Conformity:	

REFERENCES	
IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-

