

PRODUCT DATASHEET LED VALUE Superstar Dowlight 11 W 3000 K 4000 5000

LED VALUE SUPERSTAR DOWNLIGHT TRI COLOR | Downlight with a variety of wattages



AREAS OF APPLICATION

- Kitchens, bathrooms, living rooms and workshops
- Residential interiors
- Corridors, entrances, foyers, stairwells, elevators

PRODUCT BENEFITS

- Cost-effective
- High efficiency and reliability
- Stylish and modern design

PRODUCT FEATURES

- Three light colors selectable via slide switch
- LED downlight with integrated driver
- Type of protection: IP44
- Luminous efficacy: up to 106 lm/W



TECHNICAL DATA

Electrical data

Nominal wattage	11.00 W
Nominal voltage	220240 V
Power factor λ	0.90
Mains frequency	50/60 Hz

Photometrical data

Color temperature	3000/4000/5000 K	
Luminous flux	1300 lm	
Luminous efficacy	118 lm/W	
Standard deviation of color matching	5 sdcm	
Light color (designation)	Warm White/Cool White/Cool Daylight	
Color rendering index Ra	≥80	

Light technical data

Beam angle	90.00 °
------------	---------

Dimensions & weight

Diameter	150.0 mm
Height	62.5 mm
Product weight	260.00 g

Colors & materials

Body material Aluminum	
Product color	White
Housing color	White
Cover material	Polycarbonate (PC)

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
---------------------------	-----------

Additional product data

Mounting type	Recessed
Mounting location	Ceiling

Capabilities

Dimmable	Yes
Type of connection	Plug type C (EU)
LED module replaceable	Not replaceable

Certificates & standards

Protection class	11
Type of protection	IP44/20K

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075398016	Folding carton box 1	123 mm x 123 mm x 73 mm	242.00 g	1.10 dm³
4058075398023	Shipping carton box 12	330 mm x 330 mm x 259 mm	4637.00 g	28.21 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.