

Carlton colour Select LED Bunker

Aesthetically pleasing and functional, the new generation of Carlton bunker meets all the required of a well-designed outdoor fitting. With 3 colour temperatures in 1 robust fitting, including a bonus caged trim, this fitting offers the flexibility to customize the right look and feel for different areas in the same install.



- One-box solution - 3-in-1 colour temperature, bonus decorative caged trim, offers flexibility in look and feel
- Sturdy and robust design - made with die-cast aluminium, frosted glass diffuser and stainless steel screws
- IP54 and IK04 rated - ideal for outdoor application

COLOUR SELECT



80

CRI



IP54

Ingress Protection Rating



IK04

Impact Rating



Non - Dimmable

Dimming



2 Years

Warranty



Symmetric

Beam Distribution



120°

Beam Angle

CODE	SYSTEM POWER	EXIT LUMEN	LM/W	CCT	DIMENSIONS	LUMINAIRE COLOUR	INRUSH CURRENT	LINE CURRENT
CB2746466	9W	665lm	72lm/W	3000K	Ø180 x H95mm	Black	0.23A	0.08A
		698lm		4000K				
		667lm		6000K				
CB2746567	9W	665lm	72lm/W	3000K	Ø180 x H95mm	White	0.23A	0.07A
		698lm		4000K				
		667lm		6000K				
CB2746870	14W	1156lm	76lm/W	3000K	Ø240 x H125mm	Black	0.43A	0.12A
		1284lm		4000K				
		1189lm		6000K				
CB2746971	14W	1156lm	76lm/W	3000K	Ø240 x H125mm	White	0.43A	0.12A
		1284lm		4000K				
		1189lm		6000K				
CB2747274	9W	575lm	72lm/W	3000K	L210 x W110 x H90mm	Black	0.23A	0.07A
		606lm		4000K				
		586lm		6000K				
CB2747375	9W	575lm	72lm/W	3000K	L210 x W110 x H90mm	White	0.23A	0.07A
		606lm		4000K				
		586lm		6000K				
CB2747678	14W	996lm	76lm/W	3000K	L285 x W165 x H130mm	Black	0.43A	0.12A
		1109lm		4000K				
		1014lm		6000K				
CB2747779	14W	996lm	76lm/W	3000K	L285 x W165 x H130mm	White	0.43A	0.12A
		1109lm		4000K				
		1014lm		6000K				



CB2746567, CB2746971



CB2746466, CB2746870



CB2746567, CB2746971



CB2747375, CB2747779



CB2747678, CB2747274