



Main

Range of product	Series 56
Range	Clipsal - 56 Series
Product brand	Clipsal
Product or component type	Time switch
Device presentation	Basic element with full cover plate
Device application	Control
Colour	Grey (RAL 7035)
Plug, socket category	Low voltage
Outlet standard	Australian/New Zealand
Control button type	1 push-button

Complementary

Switch function	1-pole
Poles description	1P + N
Control type	Push-button
Number of poles	1
Device mounting	Surface
Connections - terminals	Screw terminals 4 x 1.5 mm ² rigid or stranded Screw terminals 3 x 2.5 mm ² rigid or stranded
Material	Polycarbonate: cover
Tightening torque	0.8 N.m
Local signalling	without
[Ue] rated operational voltage	250 V AC 50 Hz
Rated current	15 A 10 AX
Protection type	Without protection
Marking	Without marking
Height	101 mm
Width	101 mm
Depth	76.5 mm
Net weight	0.18 kg
Targeted country	Australia

Environment

Ambient air temperature for operation	0...25 °C
Outlet standard	Industrial
IP degree of protection	IP66 conforming to AS 60529
Standards	AS/NZS 3133 AS/NZS 3123

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.18 kg
Package 1 Height	76.5 mm
Package 1 width	99.5 mm
Package 1 Length	99.5 mm