



STARGEM III SE7080/1TC - 15W

15 watt IP65 wall mounted LED floodlight with selectable CCT

Application

A stylish solution for residential exterior spaces

Design Specifications

- Robust adjustable black or white aluminium optical head assembly
- Durable polycarbonate mounting base
- Opal polycarbonate diffuser, beam distribution 100 degree,
- Selectable CCT 3000K/4000K/5700K
- High efficiency LED optics, integral non-dimmable LED driver



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	SE7080/1TC/BK	240	15	1200/1300/1250	3000/4000/5700	80
	SE7080/1TC/WH	240	15	1200/1300/1250	3000/4000/5700	80

Beam Angle (°)	Body Colour	Dim (mm)	Mass (kg)
100	BLACK	112(W) x 138(H) x 180(D)	0.3
100	WHITE	112(W) x 138(H) x 180(D)	0.3

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

SE7080/1TC

