



ECOLINE MKII SL9732 - 12/50W

LED narrow diffused batten with selectable colour temperature and dual power

Application

Conventional linear LED batten products for commercial service spaces

Design Specifications

- 65 mm narrow steel body
- Quality white powder coat finish with robust polycarbonate diffuser
- Large terminal block, easy installation
- Easy selectable colour temperature with an inbuilt DIP switch 3000K/4000K/5700K (SL9732/TC/DP)
- High efficiency (>125lm/W) SMD LED, CRI >80, 120° beam distribution
- Integral constant current non-dimmable LED driver with selectable power, Emergency options available compliant to AS/NZS2293, corridorSTANDBY options available



Performance

Dimmable - **OPTIONAL**

Dimmer Type - **Trailing edge, 1-10V, DALI/DSI**

Technical Specification

Model No.	Input Voltage (V/AC)	Power (W)	Multiple Wattage	Lumens (lm)	CCT (K)	CRI
SL9732/20TC/C	240	20	12/20	2465/2650/2670	3000/4000/5700	80
SL9732/20TC/DP2	240			2465/2650/2670	3000/4000/5700	80
SL9732/40CW2	240	40		5000	4000	80
SL9732/40DL2	240	40		5000	5700	80
SL9732/40TC/C	240	40	24/40	4800/5180/5230	3000/4000/5700	80
SL9732/40TC/DP2	240			4800/5180/5230	3000/4000/5700	80
SL9732/50TC/DP2	240		30/50	5910/6270/6330	3000/4000/5700	80

Technical Specification

Model No.	Beam Angle (°)	Dimmable	Dim (mm)	Body Colour
SL9732/20TC/C	120	NO	600(L) x 65(W) x 65(H)	WHITE
SL9732/20TC/DP2	120	OPTIONAL	600(L) x 65(W) x 65(H)	WHITE
SL9732/40CW2	120	OPTIONAL	1135(L) x 65(W) x 65(H)	WHITE
SL9732/40DL2	120	OPTIONAL	1135(L) x 65(W) x 65(H)	WHITE
SL9732/40TC/C	120	NO	1135(L) x 65(W) x 65(H)	WHITE
SL9732/40TC/DP2	120	NO	1135(L) x 65(W) x 65(H)	WHITE
SL9732/50TC/DP2	120	NO	1500(L) x 65(W) x 65(H)	WHITE


NOTE: 50 watt model available for NZ only

NOTE: lumens (lm) shown are at FULL power setting


Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

SL9732 20



SL9732 40



Photometric Data

Unit: cd C0/C180 _____ C90/C270 _____

SL9732/20TC/DP2 at 4000K **SL9732/40TC/DP2 at 4000K**

