



Pullwire polyester mono 15 m Ø 3 mm with dispenser
The all-purpose residential pull-wire.



Characteristics

Length : **15**
Pull-wire Ø : **3**
Breakage : **80**

Benefits

- Highly rigid.
- No shape memory.
- Does not rotate on its axis.
- Ultra-slim diameter.

GENERAL INFORMATION

Technical details

Hexagonal crimping.
Includes:
Rigid head with crimped pulling eye, Ø 5 mm.
Screwed pulling eye, M5 Ø 6 mm.
Casing (BIZ 760 058).

Advice

Maximum bending diameter, 2 cm.

Application(s)

For pulling cables through 16 to 50 mm electrical ducts and conduits, even if congested and curved.
Ideal for distances up to 20 m.

LOGISTIC INFORMATION

Packaging



No packaging

Height (cm) : 8
Length (cm) : 36
Depth (cm) : 30
Net weight (kg) : 1.17
Gross weight (kg) : 1.17



Outer package 1



Carton box

Height (cm) : 35
Length (cm) : 39
Depth (cm) : 32
Net weight (kg) : 4.68
Gross weight (kg) : 5.33



Outer package 2



Pallet

Height (cm) : 119
Length (cm) : 120
Depth (cm) : 80
Net weight (kg) : 84.24
Gross weight (kg) : 110.94

