

## Pullwire nylon 20 m Ø 4 mm with dispenser

*Suitable for passing pull-wires through unobstructed environments.*



### Characteristics

Length (m) : 20  
Pull-wire Ø (mm) : 4  
Breakage (kg) : 70

### Benefits

- Flexible.
- Low shape memory.

## GENERAL INFORMATION

### Technical details

Hexagonal crimping.

Includes:

Flexible head with screwed pulling eye, M5 Ø 6 mm .  
Screwed pulling eye, M5 Ø 6 mm.

### Advice

Maximum bending diameter, 4 cm.

### Application(s)

For pulling cables through 16 to 25 mm electrical ducts and conduits.  
Ideal for distances up to 20 m.

## LOGISTIC INFORMATION

### Packaging



#### No packaging

Height (cm) : 8  
Length (cm) : 36  
Depth (cm) : 30  
Net weight (kg) : 1.3  
Gross weight (kg) : 1.3



### Outer package 1



#### Carton box

Height (cm) : 35  
Length (cm) : 39  
Depth (cm) : 32  
Net weight (kg) : 5.2  
Gross weight (kg) : 5.85



x 4.00

### Outer package 2



#### Pallet

Height (cm) : 119  
Length (cm) : 120  
Depth (cm) : 80  
Net weight (kg) : 93.6  
Gross weight (kg) : 120.3



x 72.00