

# PRODUCT DATASHEET LED PFM BULKHEAD CIRCULAR 13W 4000K

LED PERFORMANCE ALUMINIUM BULKHEAD | Aluminium bulk head family with high IP rating



#### Areas of application

- Workshops, garages, covered outdoor storage areas
- Gardens, balconies and other outdoor areas

#### **Product benefits**

- Compact and robust design
- Motion sensor version available
- Stylish and modern design

## **Product features**

- Die-cast aluminum housing with PC front cover

Impact resistance: IK07Type of protection: IP54



# **TECHNICAL DATA**

# Electrical data

Nominal wattage	13.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	60.000 mA
Protection class	1

## Photometrical data

Luminous flux	950 lm
Luminous efficacy	75 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	≥80

# **Dimensions & Weight**

Diameter	220.00 mm
Height	70.00 mm
Product weight	810.00 g

# Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Cover material	Plastic
Mercury content	0.0 mg

# **Application & Mounting**

Type of connection	Terminal
Type of protection	IP54
Dimmable	No
Mounting type	Surface
Application environment	Outdoor
LED module replaceable	Not replaceable

# **DOWNLOAD DATA**

D	DOWNLOAD DATA
PDF U	Jser instruction
<b>—</b> т	Fender documents
	ES file (IES)

## **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075388062	Folding box 1	231 mm x 81 mm x 231 mm	942.00 g	4.32 dm <sup>3</sup>
4058075388079	Shipping box 12	487 mm x 262 mm x 482 mm	12486.00 g	61.50 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.