

PRODUCT DATASHEET LED Value Bulkhead PC 22W TRI

LED VALUE BULKHEAD PC | IP65 polycarbonate bulkhead available in single CCT and TRI CCT



Areas of application

- Gardens, balconies and other outdoor areas
- Basements, garages, warehouses

Product benefits

- Robust design
- Homogeneous light output
- Easy to install, easy to maintain

Product features

- Housing made of durable polycarbonate
- Type of protection: IP65



TECHNICAL DATA

Electrical data

Nominal wattage	22.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Protection class	Ш

Photometrical data

Color rendering index Ra	≥80
--------------------------	-----

Dimensions & Weight

Diameter	330.00 mm
Height	66.00 mm
Product weight	960.00 g

Materials & Colors

Product color	Black
Housing color	Black
Body material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Type of protection	IP65	
Protection class IK (shock resistance)	IK10	
Dimmable	No	
Mounting type	Surface	
Mounting location	Wall / Ceiling	
LED module replaceable	Not replaceable	

Lifespan

Lifespan L70/B50 at 25 °C 30000 h

DOWNLOAD DATA

DOWNLOAD DATA

PDF

User instruction

	DOWNLOAD DATA
1	Tender documents
1	IES file (IES)

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075391796	Folding box 1	344 mm x 332 mm x 72 mm	1157.00 g	8.22 dm ³
4058075391802	Shipping box 10	687 mm x 362 mm x 377 mm	12530.00 g	93.76 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.