

PRODUCT DATASHEET

LED Performance Bulkhead 19 W/4000 K

LED PERFORMANCE BULKHEAD IK10 | IP65 robust bulkhead with motion sensor and emergency lighting function



Areas of application

- Gardens, balconies and other outdoor areas
- Basements, garages, warehouses

Product benefits

- Robust design
- Homogeneous light output
- Easy to install, easy to maintain

Product features

- Impact resistance: IK10
- Housing made of durable polycarbonate
- Type of protection: IP65



TECHNICAL DATA

Electrical data

Nominal wattage	19.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Protection class	II

Photometrical data

Luminous flux	1600 lm
Luminous efficacy	84 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	> 80

Dimensions & Weight

Diameter	351.00 mm
Height	85.00 mm
Product weight	1280.00 g

Materials & Colors

Product color	Black
Housing color	Black
Body material	Polycarbonate (PC)
Mercury content	0.0 mg




Application & Mounting

Type of protection	IP65
Protection class IK (shock resistance)	IK10
Dimmable	No
Mounting type	Surface
Mounting location	Wall / Ceiling
LED module replaceable	Not replaceable

Lifespan

Lifespan L70/B50 at 25 °C	30000 h
---------------------------	---------

DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction
	Tender documents
	IES file (IES)

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075391918	Folding box 1	294 mm x 284 mm x 78 mm	1304.00 g	6.51 dm ³
4058075391925	Shipping box 10	750 mm x 425 mm x 715 mm	13733.00 g	227.91 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.