

# PRODUCT DATASHEET

## LED Performance Bulkhead 20 W/4000 K

LED PERFORMANCE BULKHEAD IK10 | IP65 robust bulkhead with motion sensor and emergency lighting function



---

### Areas of application

- Gardens, balconies and other outdoor areas
- Basements, garages, warehouses

---

### Product benefits

- Robust design
- Homogeneous light output
- Easy to install, easy to maintain

---

### Product features

- Impact resistance: IK10
- Housing made of durable polycarbonate
- Type of protection: IP65



---

## TECHNICAL DATA

### Electrical data

Nominal wattage	20.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Protection class	II

### Photometrical data

Luminous flux	1600 lm
Luminous efficacy	80 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	> 80

### Dimensions & Weight

Diameter	351.00 mm
Height	85.00 mm
Product weight	1320.00 g

### Materials & Colors

Product color	Black
Housing color	Black
Body material	Polycarbonate (PC)
Mercury content	0.0 mg

### Application & Mounting



Type of protection	IP65
Protection class IK (shock resistance)	IK10
Dimmable	No
Mounting type	Surface
Mounting location	Wall / Ceiling
LED module replaceable	Not replaceable

### Lifespan

Lifespan L70/B50 at 25 °C	30000 h
---------------------------	---------

---

## DOWNLOAD DATA

DOWNLOAD DATA	
	Tender documents
	IES file (IES)

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075391932	Folding box 1	294 mm x 284 mm x 78 mm	1574.00 g	6.51 dm <sup>3</sup>
4058075391949	Shipping box 10	750 mm x 425 mm x 715 mm	16433.00 g	227.91 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.