

BWP ECO LED Weatherproof Batten Gen 2

The high output LED weatherproof batten has longer life and the ability to select your preferred lumen output/wattage within one light fitting.

- Wide Polycarbonate body to cover old footprint
- Robust and lockable stainless steel clips on body
- Easy installation with large terminal block, stainless steel mounting clips, 20mm cable gland and one optional knock-out at the opposite end



LUMEN^{SELECT} | COLOUR^{SELECT}



80

CRI



IP65

Ingress
Protection
Rating



IK08

Impact Rating



5SDCM

MacAdam
Steps



54,000hrs
(L70/B50)

Lifetime



3 Years

Warranty



100°

Beam Angle


CODE	SYSTEM POWER	EXIT LUMEN	EFFICACY	CCT	DIMENSIONS	WEIGHT	INRUSH CURRENT	SENSOR TYPE
BWPECO202ECS	18W	2500lm	138lm/W	4000K	L655 x W130 x H92mm	1kg	10A	
		2100lm	116lm/W	3000K				
		2100lm	116lm/W	6000K				
BWPECO404ECSLS	40W	5200lm	117lm/W	4000K	L1265 x W130 x H92mm	2kg	12A	
		33W	4200lm	118lm/W				4000K
		27W	3400lm	133lm/W				6000K
		20W	2500lm	125lm/W				3000K
		27W	3400lm	125lm/W				3000K
		33W	4000lm	121lm/W				3000K
		20W	2700lm	135lm/W				4000K
		27W	3600lm	133lm/W				4000K
		20W	2500lm	125lm/W				6000K
		33W	3900lm	118lm/W				6000K
		40W	4600lm	115lm/W				6000K
		40W	4700lm	117lm/W				3000K
		BWPECO404ECSS	40W	4737lm				118lm/W
BWPECO505ECS	52W	6200lm	119lm/W	4000K	L1565 x W130 x H92mm	2kg	13A	
		5900lm	113lm/W	3000K				
		5700lm	109lm/W	6000K				

ACCESSORY CODE


DESCRIPTION

PRC05

REMOTE CONTROL FOR PROGRAMMING PIERLITE SENSORS (TYPE 05)



BWPECO202ECS



BWPECO404ECSLS, BWPECO404ECSS



Product Images



BWPECO404ECSLS, BWPECO404ECSS



BWPECO505ECS