## 5041NMS

Push button inteface, C-Bus, 40 Series module, slave



Main	
Range	C-Bus
Product brand	Clipsal
Product name	Series 40M
Product or component type	Push-button interface
Device application	Control
Colour	Transparent green
Switch application	Load switching Dimming up/down control Timer Scene control Bell switch Shutter control Fan speed control Blind control

Complementary

C-Bus	
Iconic wall plate	
255 possible levels	
Wall mounted by Series 40M grid	
1536 V DC	
100 kOhm at 1 kHz	
LED (red/blue)status:	
Twisted unshielded pairs cable category 5e	
3.75 kV from C-Bus to mains	
C-Bus via 40 series master module	
Slave	
Push-button	
14.5 mm	
22.8 mm	
22.8 mm	
0.007 kg	
Plastic	
5 s	
Programmed with learn mode	
Programmed with C-Bus software	
1s18h12m15s	
18 mA	
	Iconic wall plate  255 possible levels  Wall mounted by Series 40M grid  1536 V DC  100 kOhm at 1 kHz  LED (red/blue)status:  Twisted unshielded pairs cable category 5e  3.75 kV from C-Bus to mains  C-Bus via 40 series master module  Slave  Push-button  14.5 mm  22.8 mm  22.8 mm  0.007 kg  Plastic  5 s  Programmed with learn mode  Programmed with C-Bus software  1s18h12m15s

## **Environment**

Ambient air temperature for operation	045 °C
Relative humidity	1095 % non-condensing
Product certifications	RCM
Standards	AS/NZS CISPR 15
	AS/NZS CISPR 14-1
	AS/NZS 60669.2.1

## Offer Sustainability

REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	☐ China RoHS Declaration