





VISTA linkable

VISTA-LK18W12

SAP CODE: 2001922



Photometric Diagram



Unit: cd
 - C0/180 144.7deg
 - C90/270 112.6deg

1200mm, 18W, Tritone, On/Off switch, Linkable slim LED batten

VISTA-LK is slimline linkable LED battens come with tricolour selection and mounting accessories that allows for quick and easy connection and installation

Accessories

BRACKET; END CAP

KEY INFORMATION

Lumen Output	1700 / 2040 / 2000lm
Input Power	18W
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	Non-Dimmable
Fitting Colour	WHITE
Warranty	4yr
IP Rating	IP20
IK Rating	N/A
IC Rating	N/A
Rebate Scheme Approvals	N/A

PHOTOMETRIC

Efficacy	94 / 113 / 111lm/W
LED	SMD
CCT	3000 / 4000 / 5700K
CRI	>90
Beam Angle	120°

ELECTRICAL

Driver	Integral
Supply Input	220-240V, 50/60Hz
Driver Output Voltage	80VDC
Power Factor	>0.9
LED Input Current (nominal)	220mA
Useful life @Ta25° (L70)	50,000hr

CONSTRUCTION

Housing	Polycarbonate
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	Mounting Bracket
Connection Type	1m Flex & Plug
Total Weight	0.35kg
Dimensions	1185.5 x 29 x 36mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 2