



Nylon pull-wire fix ed endings pulling eye and flexible head with pulling eye 20 m Ø 4 mm without casing

Suitable for passing through unobstructed environments.



Characteristics

Length (m) : 20
Pull-wire Ø (mm) : 4
Breakage (kg) : 70

Benefits

- Very flexible.
- Low shape memory.

GENERAL INFORMATION

Technical details

Hexagonal crimping.
Includes:
Flexible head with screwed pulling eye, M5 Ø 6 mm .
Screwed pulling eye, M5 Ø 6 mm.

Advice

Maximum bending diameter, 4 cm.

Application(s)

For pulling cables through 16 to 25 mm electrical ducts and conduits.
Ideal for distances up to 20 m.

LOGISTIC INFORMATION

Packaging



Color sticker

Height (cm) : 30
Length (cm) : 30
Depth (cm) : 3
Net weight (kg) : 0.31
Gross weight (kg) : 0.31



Outer package 1



Carton box

Height (cm) : 60
Length (cm) : 32
Depth (cm) : 32
Net weight (kg) : 10.7
Gross weight (kg) : 11.4



Outer package 2



Pallet

Height (cm) : 113
Length (cm) : 120
Depth (cm) : 80
Net weight (kg) : 128.1
Gross weight (kg) : 148.7

