



ARGO-600-EM

CLEVERTRONICS ECONOMY ARGO LED WEATHERPROOF BATTEN
WITH SWITCHABLE COLOUR



PRODUCT INFORMATION

Part Number	ARGO-600-EM
MIC	AUB03520120001
Description	Economy ARGO 600mm LED Weatherproof Batten with Switchable Colour
Construction	Polycarbonate Base and Diffuser with Captive Stainless-Steel Clips (SS301)
Mounting	Surface mount
Dimensions L x W x H	655mm x 121mm x 88mm
Weight	1.5 kg
Diffuser	Polycarbonate
Driver / Ballast	LED Driver – 20w Stallion
Lamp(s)	Dual LED strip module, 3,000K warm white, 5,700K cool white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Total lumen output	2150lm (120lm/W @4000K, based on non-emergency), details see table below
Power Consumption	see table below
IP Rating	IP65
Operating Temperature	0°C to 40°C
Impact Rating	IK08
AS2293 Classification	C ₀ =D40 C ₉₀ =D25
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560150	BATT:LiFePO4 3.2V 3.0Ah 70mm lead,noBRKT
ELIFE-X-LI-CKIT-2LED-SL-NP	Lifelight, Control Only,2LED,3.0Ah,325mA
1330086-A	LED Driver - 20w Stallion, S-MNT
8002848	PCA: LED Strip for 2ft Argonaut Tri-Colour (x2)

Colour	Power Consumption			Total Lumen Output
	MAX Charge Lamp ON	Standby Lamp ON	Standby Lamp OFF	
3000K	20 W	19 W	0.4 W	1950 lm
4000K	19 W	18 W	0.4 W	2150 lm
5700K	20 W	19 W	0.4 W	2040 lm

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order