



VISTALITE

VSL20W40W12-TRI

SAP CODE: 2001634




20/40W Tritone indoor LED batten

A diffused appearance LED batten with a choice of 3 colour temperatures and dual intensity.



Photometric Diagram



Unit: cd
 - C0/180 120.0deg
 - C90/270 120.0deg

KEY INFORMATION

Lumen Output ^{40W}	4220 / 4540 / 4610lm
^{20W}	2100 / 2330 / 2390lm
Input Power	40W
Hole Cutout Size	N/A
Install	SUSPENDED, SURFACE MOUNT
Dimming Options	Non-Dimmable
Trim Colour	WHITE
Warranty	4yr
IP Rating	IP40
IK Rating	N/A
IC Rating	N/A
Rebate Scheme Approvals	Pending Approval ETA Mid October

PHOTOMETRIC

Efficacy ^{40W}	105 / 113 / 115lm/W
^{20W}	105 / 117 / 119lm/W
LED	SMD
CCT	4000 / 4700 / 5700K
CRI	>80
Beam Angle	120°

ELECTRICAL

Driver	Integral
Supply Input	220-240V, 50/60Hz
Driver Output Voltage	27-37VDC
Power Factor	>0.9
LED Input Current (nominal)	700-1050mA
Useful life @Ta25° (L70)	50,000hr

CONSTRUCTION

Housing	Powder Coated Steel
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	N/A
Connection Type	Terminal Block
Total Weight	1.8kg
Dimensions	1205 x 68 x 68mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1