SMOKE DETECTOR - PHOTOELECTRIC



240V - 10 YR LITHIUM BATTERY

FEATURES & BENEFITS

- Discrete slimline appearance
- Premium quality and design
- Interconnectable with up to 24 units (wired 150m max, wireless 60m max)
- Compatible with FSA-50000 Wireless Interconnect Module, for wireless interconnection with FSA-30000
- 3V DC 10 year lithium battery
- Separate hush/test button
- Hinged detachable base easy push button open
- 'No Battery', 'No Close' feature
- Loop terminal provided
- Mounting holes line up with standard plaster brackets
- Base recessed for mains cabling no need for large ceiling cut-away
- LED indicators
- 'Low Battery' audible warning
- 5 Year Warranty
- Improved resilience to EMI interference
- Compatible with FSA-90000 remote controller

SPECIFICATIONS

Sound level output: 85db Temperature range: 0 - 40°C Humidity Range: 10% - 93%

Dimensions: 132mm Ø x 43mm (H)

Conforms to: AS3786:2014







COMPLIES WITH AS3786:2014 OPTIONAL WIRELESS INTERCONNECT CAPABILITY

Code	Description	Packing	MOQ	Ctn
FSA-60000	Photoelectric Smoke Detector - 240V 10 Year Lithium Battery	1	1	30



