

Flexion G2 - 5M Kit

STANDARDS



The FLEXION G2 range of LED strips can be cut and easily mounted making it suitable for indoor feature lighting. It is available in 3 levels of intensity; high, medium or low.

- Easy to install flexible LED strip
- 5m roll with LED driver
- Complete with flex and plug for ease of installation
- Phase cut dimming options available on request
- 24V Extra low safe voltage
- Further reduced trimmable length (*at indicated points*)
- Secure with adhesive backing to clean smooth surface
- Optional dimmable drivers available

SPECIFICATIONS

FLEXION G2 - 5M KIT

WATTS	FEATURE	IP RATING	LEDs per meter	CUTTING INTERVALS	LUMEN PER METER	lm/W	CCT	SAP CODE	PRODUCT CODE
25W	Low Intensity 5 W/m (power per meter)	IP20	60	100mm	531lm	105lm/w	3000K	2002017	FX25W5M3K-IP20
			60	100mm	533lm	105lm/w	4000K	2002015	FX25W5M4K-IP20
			60	100mm	510lm	105lm/w	6500K	2002013	FX25W5M6K-IP20
		IP65	60	100mm	505lm	105lm/w	3000K	2002018	FX25W5M3K-IP65
			60	100mm	514lm	105lm/w	4000K	2002016	FX25W5M4K-IP65
			60	100mm	494lm	105lm/w	6500K	2002014	FX25W5M6K-IP65
40W	Medium Intensity 8 W/m (power per meter)	IP20	120	50mm	668lm	100lm/w	3000K	2002023	FX40W5M3K-IP20
			120	50mm	696lm	100lm/w	4000K	2002021	FX40W5M4K-IP20
			120	50mm	706lm	100lm/w	6500K	2002019	FX40W5M6K-IP20
		IP65	120	50mm	626lm	100lm/w	3000K	2002024	FX40W5M3K-IP65
			120	50mm	585lm	100lm/w	4000K	2002022	FX40W5M4K-IP65
			120	50mm	521lm	100lm/w	6500K	2002020	FX40W5M6K-IP65
75W	High Intensity 15 W/m (power per meter)	IP20	160	31.25mm	1299lm	90lm/w	3000K	2002029	FX75W5M3K-IP20
			160	31.25mm	1463lm	90lm/w	4000K	2002027	FX75W5M4K-IP20
			160	31.25mm	1415lm	90lm/w	6500K	2002025	FX75W5M6K-IP20
		IP65	160	31.25mm	1135lm	90lm/w	3000K	2002030	FX75W5M3K-IP65
			160	31.25mm	1158lm	90lm/w	4000K	2002028	FX75W5M4K-IP65
			160	31.25mm	996lm	90lm/w	6500K	2002026	FX75W5M6K-IP65