



## SOL SL9726 -10/42W

IP65 LED weatherproof batten with dual colour selections

### Application

Commercial or industrial utility applications requiring IP65 and IK08 performance

### Design Specifications

- Dual colour selections Blue or Green, Red or Amber
- Rounded profile design, robust polycarbonate body and UV stabilized polycarbonate diffuser
- Stainless steel clips & screws, 20mm cable gland entry
- Integral constant current non-dimmable LED driver
- CorridorSTANDBY options available
- Wavelength / CCT - Blue: 450 - 470 nm, Green: 510 - 530 nm, Amber: 1800 K, Red: 615 - 635 nm



### Performance

Dimmable - **OPTIONAL**  
In Built Sensor - **OPTIONAL**  
Sensor Type - **MICROWAVE**

### Technical Specification

Model No.	Description	Input Voltage (V/AC)	Multiple Wattage	Beam Angle (°)	Body Colour	Dim (mm)
SL9726/20AM/RD	WEATHERPROOF 642mm IP65 20W AMBER/RED	240	10/20	120	GREY	642(L) x 118(W) x 77(H)
SL9726/20BU/GN	WEATHERPROOF 642mm IP65 20W BLUE/GREEN	240	10/20	120	GREY	642(L) x 118(W) x 77(H)
SL9726/40BU/GN	WEATHERPROOF 1251mm IP65 42W BLUE/GREEN	240	20/42	120	GREY	1251(L) x 118(W) x 77(H)
SL9726/40AM/RD	WEATHERPROOF 1251mm IP65 42W AMBER/RED	240	20/42	120	GREY	1251(L) x 118(W) x 77(H)

Product orders are subject to a MOQ

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



## Product Images

